



# DURALUX SERIES SALES SHEET

## DURALUX LED WORK LIGHT

High Performance LED Work Light





DURA-660 Shown

DURA-460 Shown

### Duralux Series

The Duralux Series is combines durability and affordability for on-the-job light.



ITEM #	DURA-610	DURA-610KIT	DURA-640	DURA-660
PART # (Stock Code)	9891125		9888378	9888385
BEAM PATTERN	10° Narrow	10° Narrow	40° Wide	60° Extra Wide
INCLUDES	1 Light & Pigtail	2 Lights & Harness	1 Light & Pigtail	1 Light & Pigtail

### Technical Information

WARRANTY	Extended
RAW LUMENS	2,958 lm
EFFECTIVE LUMENS	2,071 lm
WATTAGE	30
WEIGHT	2.10 lb/0.95 kg
LED LIFESPAN	50,000 Hours
DIMENSIONS	5.39" x 2.57" x 4.28" 136.7 mm x 69 mm x 106.5 mm
INPUT VOLTAGE	11-65V DC
AMP DRAW (12V)	2.5A
IP RATING	IP-68
VIBRATION RATING	8.6 G <sub>rms</sub>
OPERATING TEMP	-40 Celsius ~ +80 Celsius

### Features

- Reduced Power Draw Reduces Wear on Associated Parts
- Reduced Power Draw Can Lead to Fuel Savings
- Low Power Consumption at Just 1.6A (12V)
- More Light Than a 100W Halogen
- Long Lasting Aluminum Housing
- Industrial Grade Warranty



ITEM #	DURA-410	DURA-410KIT	DURA-440	DURA-460
PART # (Stock Code)	9891132	9891187	9141619	9141527
BEAM PATTERN	10° Narrow	10° Narrow	40° Wide	60° Extra Wide
INCLUDES	1 Light & Pigtail	2 Lights & Harness	1 Light & Pigtail	1 Light & Pigtail

### Technical Information

WARRANTY	Extended
RAW LUMENS	1,972 lm
EFFECTIVE LUMENS	1,380 lm
WATTAGE	20
WEIGHT	1.50 lb/ 68 kg
LED LIFESPAN	50,000 Hours
DIMENSIONS	3.94" x 2.57" x 4.24" 100 mm x 65.5 mm x 107.6 mm
INPUT VOLTAGE	11-65V DC
AMP DRAW (12V)	1.67A
IP RATING	IP-68
VIBRATION RATING	8.6 G <sub>rms</sub>
OPERATING TEMP	-40 Celsius ~ +80 Celsius

### Features

- Reduced Power Draw Reduces Wear on Associated Parts
- Reduced Power Draw Can Lead to Fuel Savings
- Low Power Consumption at Just 1.6A (12V)
- DURAE-490 Available with E-mark Approval
- More Light Than a 100W Halogen
- Weatherproof Deutsch Connector
- Die-Cast Aluminum Housing

