



XPI LED LIGHT BAR


XPI LED LIGHT BAR

Projects Usable Light Further Than Ever Before Possible



Xmitter Prime Iris (XPI) Series

The XPI Series uses Vision X's IRIS Reflectors to achieve unmatched distance. XPI Light bars come standard with both Patented Feet Mount or End Mount.



XPI-15M Shown

ITEM #	XPI-6	XPI-12M	XPI-15M	XPI-18M	XPI-21M	XPI-24M	XPI-27M
PART # (Stock Code)	9889399	9889405	9889443	9889412	9890500	9889429	9889436
L.E.D.S	6	12	15	18	21	24	27
LENGTH	11.50"/291mm	24.00"/611mm	29.40"/746mm	34.70"/881mm	40.00"/1,016mm	45.3"/1,151mm	50.6"/1,286mm
BEAM	Straight	3x Tilting Each End	3x Tilting Each End	3x Tilting Each End	3x Tilting Each End	3x Tilting Each End	3x Tilting Each End
RAW LUMENS	3,168 lm	6,336 lm	7,920 lm	9,504 lm	11,088 lm	12,672 lm	14,256 lm
EFFECTIVE LUMENS	2,218 lm	4,436 lm	5,545 lm	6,654lm	7,762 lm	8,872 lm	9,981 lm
WATTAGE	30	60	75	90	105	120	135
AMP DRAW (12V)	2.5A	5A	6.25A	7.5A	8.75A	10A	11.25A
WEIGHT	3.09 lb/1.4kg	6.61 lb /3kg	7.94 lb/3.6kg	9.37 lb/4.25kg	10.80 lb/4.9kg	12.35 lb/5.6kg	13.67 lb/6.2kg

Technical Information

WARRANTY	Extended
LED LIFESPAN	6.71 lbs/3.04 kg
HEIGHT	2.80"/72mm
DEPTH	3.18"/81mm
MOUNTING DEPTH	1.00"/25mm
INPUT VOLTAGE	11-32V DC
IP RATING	IP-69K
VIBRATION RATING	15.6G _{RMS}
OPERATING TEMP	-40 C~ +80 C

Features

- Dual Mounting Options Standard (patented feet mount or end mount)
- Proprietary IRIS Reflector Technology Featuring Tilting Reflectors
- Tilting Reflectors Provide Mixed/Combo Beam Spread
- Xtreme Five Watt LED is Driven to 90% Efficiency
- Integrated Electronic Thermal Management
- Weatherproof Deutsch Connector
- Polycarbonate Lens
- Patent Pending

* No Harness is Included With This Product