



# CANNON SALES SHEET

## CANNON 25 WATT LED DRIVING LIGHT

**New Generation Technology Produces over 1000' of Usable Light**



### PROPRIETARY IRIS REFLECTOR TECHNOLOGY HYBRID ALUMINUM POLY CARBONATE HOUSING

- Integrated Electronic Thermal Management (ETM)
- Prime Drive for Enhanced Reliability and Output
- Snap-On Covers Allow Easy Change of Beam
- Ultra Light Weight 2 lb Hybrid Construction
- Two Light Kits Available

### 10° Narrow Beam Lights

PART #	CTL-CPZ110	CTL-CPZ110KIT
COLOR	Black	Black
INCLUDES	1 Light & Pigtail	2 Lights & Harness



0 m 100 m 200 m 300 m 400 m 450 m

### Snap-On Protective Covers

PART #	PCV-CP1	PCV-CP1Y	PCV-CP1R	PCV-CP1B	PCV-CP1BL
COLOR	Clear	Yellow	Red	Blue	Black Out
BEAM PATTERN	Protective Cover	Protective Cover	Protective Cover	Protective Cover	Protective Cover

### Snap-On Euro Beam Covers

PART #	PCV-CP1EU	PCV-CP1YEU	PCV-CP1REU	PCV-CP1BEU
COLOR	Clear	Yellow	Red	Blue
BEAM PATTERN	Euro	Euro	Euro	Euro

### Snap-On Flood Beam Covers

PART #	PCV-CP1FL	PCV-CP1YFL	PCV-CP1RFL	PCV-CP1BFL
COLOR	Clear	Yellow	Red	Blue
BEAM PATTERN	Flood	Flood	Flood	Flood



### SPECIFICATIONS

WARRANTY	Extended
AVAILABLE HOUSING COLOR(S)	Black
AVAILABLE BEAM PATTERNS	10°, Snap-On Filters Available
RAW LUMENS	2,500 lm
EFFECTIVE LUMENS	1,750 lm
WATTAGE	25
WEIGHT	2.02 lb/920 g
LED LIFESPAN	50,000 Hours

### IMAGES

FRONT	SIDE

### TECHNICAL DETAILS

DIMENSIONS	4.72" x 4.36" x 5.75" 120 mm x 110.7 mm x 146 mm
OPTIC PURITY	90%
DRIVEN AT	90%
INPUT VOLTAGE	9-32V DC
AMP DRAW (12V)	2.08A
IP RATING	IP-68
VIBRATION RATING	15.6 G <sub>rms</sub>
OPERATING TEMP	-40 Celsius ~ +85 Celsius

### ADDED FEATURES

- Weatherproof Deutsch Connector
- Kits with Two Lights and Harness Available
- Poly Carbonate Housing
- Polycarbonate Lens

50 m

30 m

10 m

-10 m

-30 m

-50 m

