



DRIFT STROBE 3 LED SERIES

DESCRIPTION

The Drift Strobe Series is designed with enhanced visibility down narrow passageways. Necessary for placement on both the front and rear of the vehicle, the drift strobe is built with a focused beam to aim at the top of the drift notifying oncoming traffic up to 200 feet sooner than a conventional strobe without blinding either operator.

Features and Benefits:

- Durable Die-Cast Housing Construction
- Four Colored LED Options
- Reverse Polarity Protection
- 15.6 Grms Vibration Rating



SPECIFICATIONS

MECHANICAL

Fixture Weight:	2.62 lbs (1.19kg)
Shipping Weight:	4.03 lbs (1.83kg)
Mounting:	Dual M6 Stud Mount

TECHNICAL

LED:	3W (CREE) XPE-2
Raw Lumens:	Varies by Color
Wattage:	9W
Wattage Per LED:	3W
Amp Draw:	0.6A @12V
Color Temperature:	Varies by Color
Operating Voltage:	9-32V DC
Operating Temperature:	-40°C ~ 80°C
Lifespan:	50,000 hrs
Polarity:	Reverse Polarity Protection
Connector:	2 Pin Deutsch

CONSTRUCTION

Housing:	Die-Cast 6061 Aluminum
Finish:	Gloss Black
Lens:	Polycarbonate

RATINGS

EMC Emission:	(CISPR 25) Edition 3.0 (2008-03) Class 3
Ingress Protection:	IP-68
Vibration Rating:	15.6 Grms
Warranty:	3 Years

ITEM #:	PART#	BEAM PATTERN
XIL-LP625R.2HZ	9888019	Red
XIL-LP625G.2HZ	9887845	Green
XIL-LP625B.2HZ	9887838	Blue
XIL-LP625A.2HZ	9888002	Amber



2D DRAWING:

