



CORROSION RESISTANT

LED LIGHTING SERIES





The Corrosion Resistant Series from Vision X consists of the 10-Watt, 50-Watt, 140-Watt, and 280-Watt LED lighting fixtures. Each fixture is designed to withstand high-risk environments where aluminum housings are susceptible to rapid deterioration due to chemicals exposed from processing plants.

All products are subjects to rigorous product testing to ensure long term durability.

- ✓ Plastic Tri-Coated Aluminum
- IP68/69K Rated
- Polycarbonate Lens
- **UL** Certified
- 50,000 Hrs Life Span
- 5 Year Warranty
- UL1598a Rated for Wet Locations
- ✓ For Acid Mist Environments

50-WATT JUNCTION BOX

140-WATT AC LIGHT

All-In-One LED Light





PROTECTIVE TRI-COATING

The secondary yellow plastic coating on the aluminum housing ensures the light fixture is corrosive resistant to high-risk environments. With the plastic tri-coated housing, the light fixture is protected from rapid deterioration from acid mist environments resulting in less maintenance and long term illumination.



EASY INSTALLATION

Making any electrical replacements a breeze, the quick connect cable allows for a simple and speedy lighting install.

STAINLESS STEEL HARDWARE

Upgraded stainless steel trunnion bracket, fasteners, and quick connect specifically to withstand chemically harsh environments.



280-WATT AC LIGHT





TECHNICAL:

Lumens:	1,000 lm
Wattage:	10W
Operating Voltage:	90-264V AC 127-370V DC
Operating Temp:	-40°C ~ 60°C
Amp Draw:	0.09A@115V AC 0.04A @ 230V AC 0.04 @ 277V AC
Beam Pattern:	180° Ultra Wide Flood with Frosted or Clear Lens
Fixture Weight:	2 lbs.

ITEM#: LSYSM40180F (180° Optics)



TECHNICAL:

Lumens:	7,000 lm
Wattage:	50W
Operating Voltage:	90-305V AC 127-431V DC
Operating Temp:	-40°C ~ 60°C
Amp Draw:	0.43A@115V AC 0.22A @ 230V AC 0.18 @ 277V AC
Beam Pattern:	180° Ultra Wide Flood
Fixture Weight:	8 lbs.

ITEM#: **LSY0225180QC** (180° Optics) ITEM#: **LSY033060QC** (60° Optics) ITEM#: **LSY033090QC** (90° Optics)



TECHNICAL:

Lumens:	21,000 lm
Wattage:	140W
Operating Voltage:	90 - 305VAC 127 - 431VDC 180-528VAC High Voltage Available
Operating Temp:	-40°C ~ 60°C
Amp Draw:	1.22A @ 115VAC 0.61A @ 230VAC 0.51A @ 277VAC
Beam Pattern:	60° 90°
Fixture Weight:	24 lbs.

ITEM#: LSY063060STRQC (60° Optics) ITEM#: LSY063090STRQC (90° Optics)



TECHNICAL:

Lumens:	36,000 lm
Wattage:	280W
Operating Voltage:	90 - 305VAC 127 - 431VDC 180-528VAC High Voltage Available
Operating Temp:	-40°C ~ 60°C
Amp Draw:	2.43A @115VAC 1.22A @ 230V AC 1.01A @ 277VAC
Beam Pattern:	60° 90°
Fixture Weight:	37.05 lbs.

ITEM#: LSY066060STRQC (60° Optics) ITEM#: LSY066090STRQC (90° Optics)



SX/EW PLANTS



VISION X USA

1601 Boundary Blvd Auburn WA 98001 United States of America P: 253-218-2900 www.vxindustrial.com



VISION X ASIA

23-7 Dongtansandan 9-gil Dongtan-myeon Hwaseong-si Gyeonggi-do 18487, Korea P: 82-32-515-4814 www.visionxlighting.com