

DESCRIPTION

The Bow Hull Light Kit offers a powerful LED light module and long range beam pattern for maritime applications. Available with two mounting options: surface mount to hull with four mounting bolts for boats designed with a pronounced flare, or weld the light directly to the hull (aluminum boats only).

SPECIFICATIONS

MECHANICAL:

Fixture Weight:	3.5 lbs (1.59 kg)
Shipping Weight:	4.6 lbs (2.09 kg)
Mounting:	4 Bolts or Welded

LED:

LED:	XD16 (Cree) x6
Lumens:	4,004 lm
Lifespan:	50,000 hr
Distance:	490 ft 149.5 M

TECHNICAL:

Wattage: 33W Amp Draw: 5.5A@12V 2.76A@24V Color Temperature: 5000K White Operating Voltage: 9-32V DC	Beam Pattern:	25°
Amp Draw: 2.76A@24V Color Temperature: 5000K White Operating Voltage: 9-32V DC	Wattage:	33W
Operating Voltage: 9-32V DC	Amp Draw:	******
	Color Temperature:	5000K White
	Operating Voltage:	9-32V DC
Operating Temp: $-40^{\circ}\text{C} \sim 80^{\circ}\text{C}$	Operating Temp:	-40°C ~ 80°C
Connector: 2pin Deutch	Connector:	2pin Deutch

CONSTRUCTION:

Housing:	Aluminum 356.1
Light Fixture Lens:	Polycarbonate
Light Fixture Finish:	Marine Grade White

RATINGS:

Ingress Protection:	IP-68/IP69K
Vibration Rating:	8.6 Grms
Depth Rating:	100'/30.48m

BOW HULL LIGHT KIT



ITEM #:	MOUNT	BEAM PATTERN	FINISH
MAR-BHLB	Bolt-On Mount	25°	Cast Aluminum
MAR-BHLW	Weld-On Mount	25°	Cast Aluminum
MAR-BHLB-B	Bolt-On Mount	25°	Powder Coated
MAR-BHLW-B	Weld-On Mount	25°	Powder Coated

2D DRAWING:



