



MINI INCIDENT RESPONSE CASE

PORTABLE EMERGENCY SCENE LIGHTING

DESCRIPTION

The mini incident response case features a compact storage height of only 24 inches and sets up in seconds with eight foot extensions to blanket any scene with intense light. Lasting up to 12 hours on a full charge of the self-contained power cells, this all-weather unit is the perfect portable lighting solution.

The response case (XLS) comes with three different lighting variations: 2 DURA Work 4 LED Lights, 4 Solo Pod LED Lights or 2 Utility Market Square 7 LED Lights. Producing up to 6,902 lumens, the mini incident response case is ideal for emergency response, flagging stations, roadside assistance, scene lighting and other portable lighting scenarios.

Features and Benefits

- Deploys in 30 Seconds, No Tools Required
- Self-Contained Power Cell
- 12 Hour Run Time
- Up to 8 Feet Light Extension
- Flashing Yellow LED on Base for Additional Safety

SPECIFICATIONS

Charging Input Voltage:	12V DC or 110-220V AC
Power Source:	XPC-400 - 35Ah Battery
Operating Temperature:	-40°C ~ +60°C
Charge Time:	10 Hours
LED Lifespan:	50,000 hrs
Run Time:	Up to 12 Hours
Warranty:	Standard

XLS-M2DURA460BP

Run Time:	11 Hours
Raw Lumens:	4,224 lm
Wattage:	40W

XLS-M4S1160BP

Run Time:	11 Hours
Raw Lumens:	1,720 lm
Wattage:	40W

XLS-M2UMX4460BP

Run Time:	6 Hours
Raw Lumens:	6,902 lm
Wattage:	70W



XLS-M2DURA460BP Shown

ITEM #:	PART#	LIGHT MODEL
XLS-M2DURA460BP	9891026	2 x DURA-460
XLS-M4S1160BP	9891033	4 x XIL-S1160
XLS-M2UMX4460BP	9891040	2 x XIL-UMX4460



MECHANICAL

Fixture Weight:	42 lbs (19.05kg)
Shipping Weight:	44 lbs (19.95kg)
Dimensions:	17.5" x 8.0" x 25.0" 445mm x 203mm x 65mm
Deployed Dimensions:	32" x 32" x 96" 813mm x 813mm x 2438mm



INCIDENT RESPONSE CASE

PORTABLE EMERGENCY SCENE LIGHTING

DESCRIPTION

The Incident Response Case is an all-in-one lighting unit that includes a power supply, case with handles/wheel and LED lighting. The unit makes it easy to setup instant light. The case stays charged up to 8.5 hours and is available in multiple LED configurations including two 6" Xmitter Bars, two 5" Evo Prime Bars, or four Solo Pod LED lights.

Features and Benefits

- Charge Using 110V AC Wall Outlet, Cigarette Lighter or Jumper Cables
- Provides Light Up to 8 Hours at Max Output
- Adjustable Light Heads for 360° Operation
- Self-Contained Rechargeable Power Cell
- Deploys in 30 Seconds, No Tools Required
- 12V Output Power Source

SPECIFICATIONS

Charging Input Voltage: 12V DC or 110-220V AC

Power Source: XPC-220 - 22Ah Battery

Operating Temperature: -40°C ~ +85°C

Charge Time: 10 Hours

LED Lifespan: 50,000 hrs

Run Time: Up to 12 Hours

Warranty: Standard

XLS-26BP

Run Time: 8 Hours

Raw Lumens: 2,880 lm

Wattage: 48W

XLS-2EP240BP

Run Time: 8.5 Hours

Raw Lumens: 3,200 lm

Wattage: 40W

XLS-4S1101BP

Run Time: 8.5 Hours

Raw Lumens: 3,600 lm

Wattage: 40W



ITEM #:	PART#	LIGHT MODEL
XLS-26BP	4008786	2 x XIL-80
XLS-2EP240BP	-	2 x XIL-EP240
XLS-4S1101BP	4008816	4 x XIL-S1101

Two Xmitter Model



Four Solo Model



MECHANICAL

Fixture Weight: 48 lbs (21.77kg)

Shipping Weight: 50lbs (22.67kg)

Dimensions: 22" x 13.81" x 9"
559mm x 351mm x 229mm

Deployed Dimensions: Height 96" / 2.44m