

# PRIMARY **WARNING** LED LIGHT RANGE

LED BEACONS

LED LIGHT BOXES



BE **SEEN**

BE **SAFE**

THE VISION TO GO FURTHER







**OPTITECH**

**AEROTECH®**

**AEROTECH® LIGHT BOX**

**AEROTECH® HD**

**TREMOR XD**

## WHAT SETS THE VISION X WARNING LIGHT RANGE APART?

---

Designed, Engineered and tested by Vision X to suit local market conditions. A product for every price point and application with features matched to market needs:

### DURABILITY

Ultra durable with military spec vibration resistance and ingress resistance up to IP-69K. Virtually unbreakable polycarbonate lenses. Products built to last backed by market-leading warranties.

### PERFORMANCE

Strobes in a range of sizes to suit industry needs. Up to 6x brighter than SAE minimum with SAE-approved beam patterns. Performance you need, exactly how you need it.

### COMPLIANCE

SAE, R65, R10, CISPR25, ROHS, Reach, IP. Ultra bright, smooth output which meets or exceeds all international standard, giving you more time to focus on your industry.

### VERSATILITY

Product to suit each application, available in a range of sizes and colors. Premium parts and a variety of mounting options; expertly-designed beacons for any task industrial, commercial, or more.

# INCREASE YOUR SECURITY

---





# VISION X RANGE

## Primary Warning L.E.D. Light



The Vision X range has one or more products to suit any amber applications. The more rigorous the applications the further to the right on the chart the suitable product is. This also applies to larger applications, as the vehicle gets larger, more light is required to effectively warn those around the vehicle.

### Beacon vs Light Box:

There are three main types of primary warning light, each provide different features to the user. The Vision X range has been designed so that for just about every application there is at least one beacon, one strobe and one light box that can meet the applications needs.

### LIGHT COMMERCIAL

**AEROTECH®**



P/No. AERO-85600A AERO-85606A

**AEROTECH®**



P/No. AERO-85015A

**ptitech**



P/No. OPT-85660A



### COMMERCIAL & CONSTRUCTION



AERO-85606A AERO-85612A

AERO-85017A



AERO-85015A



OPT-85660A

**AEROTECH® HD**



AERO-85620A

AERO-85618A

### INDUSTRIAL & MINING

**TREMORXD**



TREM-85246A

TREM-85250A

AERO-85017A



AERO-85019A



AERO-85620A

AERO-85618A



# VISION X QUALITY

## Visibility Upgrade Experience

---

### ENVIRONMENTAL TESTING:

The Vision X in house testing lab has extensive environmental testing equipment including thermal shock, dust, rain, temperature and humidity training. Each warning light in the Vision X range is tested to ensure it is fit for the application it is designed for as well as the conditions it will operate under.


### PHOTOMETRIC TESTING:

The Vision X warning lights are tested in-house in the Vision X light lab as well as independently certified labs to ensure they meet all the relevant standards including SAE, ECE and California title 13.

All Vision X warning lights are also tested and certified to ensure electrical safety as well as ensuring no radio frequency interference. All products adhere to ECE R10 for electrical safety and most are also CISPR25 rated for added RFI protection.

### VIBRATION TESTING:

Vibration is a major factor that can cause premature failure in emergency lighting products as they are used in the worlds harshest conditions. Vision X tests all their warning lights to international standards in independent laboratories. Where products will be used in industrial and mining applications Vision X also tests to the more stringent military standard MIL-STD-810G. This testing ensures the lamps will not fail due to the conditions they are used in. Most are also CISPR25 rated for added RFI protection.























# WARNING LIGHT

## Application Guide



### LIGHT COMMERCIAL











RANGE	PART NO.	Outdoor Forklift	Vans	Flat Beds	Sweepers	Pick-ups	Small Trucks	Traffic Management
 	OPT-85660A							
 	AERO-85600A							
 	AERO-85606A							
 	AERO-85612A							
 	AERO-85015A							
 	AERO-85017A							
 	AERO-85019A							
 	AERO-85018A							
 	AERO-85020A							
 	TREM-85246A							



COMMERCIAL & CONSTRUCTION

INDUSTRIAL & MINING

 Utility Bodies	 Maintenance Vehicles	 Light Construction	 Tractors	 Heavy Transport	 Heavy Construction	 Garbage Trucks	 Forestry	 Mining Trucks	 Mining Equipment (eg. drills)
Ideal	Ideal	Ideal	Ideal	Ideal	Ideal	Acceptable	Occasional	Not suitable	Not suitable
Acceptable	Acceptable	Acceptable	Occasional	Not suitable	Not suitable	Not suitable	Not suitable	Not suitable	Not suitable
Acceptable	Acceptable	Acceptable	Ideal	Occasional	Occasional	Occasional	Not suitable	Not suitable	Not suitable
Ideal	Ideal	Ideal	Ideal	Ideal	Acceptable	Occasional	Not suitable	Not suitable	Not suitable
Acceptable	Acceptable	Occasional	Occasional	Occasional	Not suitable	Not suitable	Not suitable	Not suitable	Not suitable
Ideal	Ideal	Acceptable	Acceptable	Acceptable	Occasional	Occasional	Occasional	Occasional	Occasional
Ideal	Ideal	Acceptable	Acceptable	Ideal	Ideal	Ideal	Ideal	Ideal	Ideal
Acceptable	Acceptable	Acceptable	Occasional	Ideal	Ideal	Ideal	Ideal	Acceptable	Acceptable
Acceptable	Acceptable	Acceptable	Occasional	Ideal	Ideal	Ideal	Ideal	Ideal	Ideal
Acceptable	Acceptable	Acceptable	Acceptable	Ideal	Ideal	Ideal	Ideal	Ideal	Ideal

Ideal

Acceptable

Occasional

Not suitable

## INDUSTRIAL & MINING



Utility  
Bodies



## Maintenance Vehicles



## Light Construction



## Tractors



Heavy  
Transport



Heavy  
Construction



# Garbage Trucks



Forestry



## Mining Trucks



Mining  
Equipment  
(eq. drills)

100

114

114

11

Not suitable






The vehicle in the image is equipped with:  
AERO-85606A

# AEROTECH<sup>®</sup> LED BEACONS

## VISIBLE, DURABLE, ADAPTABLE

AeroTech® is a family of L.E.D strobes designed to make strobe selection easy. The range features strobes to suit any amber application. The key is that no matter the strobe the three key reasons to buy remain the same. AeroTech® strobes are Visible, Durable and Adaptable.


## 4 FLASH PATTERNS



**Integrated light sensor ensures no dazzling in low light conditions (Night Mode). Sensor can be overridden if required.**

## MORE AERODYNAMIC

**The unique shape reduces drag by up to 60% which results in less high speed wind noise.**








**KEY FEATURES:****VERSATILE MOUNTING:**

Available in 3 Bolt (Flange), Single Bolt, DIN Mount, Flexible Pole Mount and Vacuum Magnetic Mount

**FLANGE****SINGLE BOLT****FIXED DIN****FLEX DIN****MAGNETIC****LIGHT COMMERCIAL | COMMERCIAL & CONSTRUCTION****TECHNICAL INFORMATION****10-33  
VOLT****SAE  
CLASS 1****CISPR 25  
CLASS 3****ECE R65  
APPROVED****ECE R10  
APPROVED****ISO 58Grms  
50G SHOCK TESTED**

MODEL	PART#	LED	MOUNTING	AMP. @12V	WATTS	WEIGHT	DIMENSION	ECE APPROVAL
	AERO-85600A	9x5W	Flange	0.6A Rot. / 1.4A Flash	45W	0.73lbs	5.31" x 5.28" x 2.68"	ECE R65 TA1, ECE R10
	AERO-85601A	9x5W	Single Bolt	0.6A Rot. / 1.4A Flash	45W	0.73lbs	5.31" x 5.28" x 2.68"	ECE R65 TA1, ECE R10
	AERO-85602A	9x5W	Fixed DIN	0.6A Rot. / 1.4A Flash	45W	0.73lbs	5.31" x 5.28" x 2.68"	ECE R65 TA1, ECE R10
	AERO-85603A	9x5W	Flex DIN	0.6A Rot. / 1.4A Flash	45W	0.73lbs	5.31" x 5.28" x 2.68"	ECE R65 TA1, ECE R10
	AERO-85604A	9x5W	Magnetic	0.6A Rot. / 1.4A Flash	45W	0.73lbs	5.31" x 5.28" x 2.68"	ECE R65 TA1, ECE R10
	AERO-85606A	18x5W	Flange	1A Rot. / 1.6A Flash	90W	0.91lbs	5.31" x 5.28" x 3.54"	ECE R65 TA2, ECE R10
	AERO-85607A	18x5W	Single Bolt	1A Rot. / 1.6A Flash	90W	0.91lbs	5.31" x 5.28" x 3.54"	ECE R65 TA2, ECE R10
	AERO-85608A	18x5W	Fixed DIN	1A Rot. / 1.6A Flash	90W	0.91lbs	5.31" x 5.28" x 3.54"	ECE R65 TA2, ECE R10
	AERO-85609A	18x5W	Flex DIN	1A Rot. / 1.6A Flash	90W	0.91lbs	5.31" x 5.28" x 3.54"	ECE R65 TA2, ECE R10
	AERO-85610A	18x5W	Magnetic	1A Rot. / 1.6A Flash	90W	0.91lbs	5.31" x 5.28" x 3.54"	ECE R65 TA2, ECE R10
	AERO-85612A	36x1W	Flange	1A Rot. / 1.6A Flash	36W	1.3lbs	5.31" x 5.28" x 5.12"	ECE R65 TA2, ECE R10
	AERO-85613A	36x1W	Single Bolt	1A Rot. / 1.6A Flash	36W	1.3lbs	5.31" x 5.28" x 5.12"	ECE R65 TA2, ECE R10
	AERO-85614A	36x1W	Fixed DIN	1A Rot. / 1.6A Flash	36W	1.3lbs	5.31" x 5.28" x 5.12"	ECE R65 TA2, ECE R10
	AERO-85615A	36x1W	Flex DIN	1A Rot. / 1.6A Flash	36W	1.3lbs	5.31" x 5.28" x 5.12"	ECE R65 TA2, ECE R10
	AERO-85616A	36x1W	Magnetic	1A Rot. / 1.6A Flash	36W	1.3lbs	5.31" x 5.28" x 5.12"	ECE R65 TA2, ECE R10

**5 YEARS**  
FUNCTION WARRANTY  
50,000 HOURS





The vehicle in the image is equipped with:  
AERO-85620A



P/No. AERO-85618A



P/No. AERO-85620A

Available in  
multiple colors:




# AEROTECH® HD HEAVY DUTY LED BEACONS

## VISIBLE, DURABLE, ADAPTABLE

Building on the AeroTech® family are the AeroTech® Heavy Duty L.E.D Strobes. These strobes are designed to be more visible and more durable making the AeroTech® range even more adaptable to any application. Designed to thrive in all conditions, especially industrial and mining conditions. These strobes suit even the biggest vehicles in the toughest conditions.


## 4 FLASH PATTERNS



Integrated light sensor ensures no dazzling in low light conditions (Night Mode). Sensor can be overridden if required.

## MORE AERODYNAMIC

The unique shape reduces drag by up to 60% which results in less high speed wind noise.





**KEY FEATURES:****COMMERCIAL & CONSTRUCTION | INDUSTRIAL****TECHNICAL INFORMATION****10-33  
VOLT**

PART#	LED	LENS COLOR	AMP. @12V	WATTAGE	WEIGHT	DIMENSION	ECE APPROVAL
AERO-85618A	18x5W	Amber	1.1A Rotate/ 2.4A Flash	90W	1.36lbs	6.10" x 6.10" x 3.94"	ECE R65 TA2, ECE R10
AERO-85620A	36x3W	Amber	1.1A Rotate/ 2.4A Flash	108W	1.94lbs	6.10" x 6.10" x 6.30"	ECE R65 TA2, ECE R10
AERO-85620B	36x3W	Blue	1.1A Rotate/ 2.4A Flash	108W	1.94lbs	6.10" x 6.10" x 6.30"	ECE R65 TA2, ECE R10
AERO-85620G	36x3W	Green	1.1A Rotate/ 2.4A Flash	108W	1.94lbs	6.10" x 6.10" x 6.30"	ECE R65 TA2, ECE R10



- Large profile for maximum visibility
- Allows more reflector space than the same sized round strobe, resulting in a wider illumination area.
- Alternating or synchronized operations of up to 6 strobe units
- 6X Brighter than SAE minimum
- SAE Class 1 and ECE R65 TA2 complied
- CISPR25 Class 3 and ECE R10 complied

**5 YEARS**  
 FUNCTION WARRANTY  
 50,000 HOURS





The vehicle in the image is equipped with:  
AERO-85019A



P/No. AERO-85015AC

P/No. AERO-85015A



P/No. AERO-85017AC

P/No. AERO-85017A



P/No. AERO-85019AC

P/No. AERO-85019A

# AEROTECH® LED LIGHT BOXES

## 6 FLASH PATTERNS

Optional Day/Night mode ensures not to dazzle in low light conditions while being ultra visible during the day.



Double Flash (SAE, ECE TA2)



Ultra (alternating flash)



Ultra (cross flash)



Rotate



Quint



Double rotate



Steady on

## VISIBLE, DURABLE, ADAPTABLE

The revolutionary AeroTech® light box range is the brightest in the Vision X range of primary warning lights. Featuring 3 sizes which can suit everything from light commercial up to transport, construction and mining applications. AeroTech® light boxes are also easy and versatile to mount because of the integrating cradle which allows mounting with or without the cradle. The range includes amber and clear lens models as well as magnetic mounting versions with over 9 feet of cable as well as in dual color.


- Vision X's most visible primary warning lights
- Ultra bright, smooth output which meets and exceeds all international standards
- Optional night mode via extra wire
- Ultra durable with extreme vibration resistance
- Versatile, easy mounting
- Available in a range of sizes and colours to suit just about any application





Amber and clear lens models available with magnetic mounting options with over 9 feet of cable.

## KEY FEATURES:



## LIGHT COMMERCIAL | COMMERCIAL & CONSTRUCTION

### TECHNICAL INFORMATION

**10-80  
VOLT**

**SAE  
CLASS 1**

**CISPR 25  
CLASS 3**

**E  
ECE R65  
APPROVED**

**ECE R10  
APPROVED**

**ISO 58Grms  
50G SHOCK TESTED**

PART#	LED	AMP. @12V	WATTAGE	WEIGHT	DIMENSION	ECE APPROVAL
AERO-85015A	54x1.5W	1.7A Rotate/ 3.5A Flash	81W	4.20lbs	6.14" x 9.84" x 2.52"	ECE R65 TA2, ECE R10
AERO-85015AC	54x1.5W	1.7A Rotate/ 3.5A Flash	81W	4.20lbs	6.14" x 9.84" x 2.52"	ECE R65 TA2, ECE R10
AERO-85017A	84x1.5W	2.1A Rotate/ 3.7A Flash	126W	4.20lbs	7.87" x 14.96" x 2.63"	ECE R65 TA2, ECE R10
AERO-85017AC	84x1.5W	2.1A Rotate/ 3.7A Flash	126W	4.20lbs	7.87" x 14.96" x 2.63"	ECE R65 TA2, ECE R10
AERO-85019A	168x1.x5W	2A Rotate/ 4.3A Flash	252W	4.55lbs	7.87" x 14.96" x 3.50"	ECE R65 TA2, ECE R10
AERO-85019AC	168x1.x5W	2A Rotate/ 4.3A Flash	252W	4.55lbs	7.87" x 14.96" x 3.50"	ECE R65 TA2, ECE R10

### MOUNTING OPTION

Magnetic mounting option rated to 120km/h



**AMBER MAGNETIC**  
PART#: AERO-85016A



**CLEAR MAGNETIC**  
PART#: AERO-85016AC

**5 YEARS**  
FUNCTION WARRANTY  
50,000 HOURS





The vehicle in the image is equipped with:  
OPT-85660A



P/No. OPT-85660A

Available in  
multiple colors:



P/No. OPT-85660AG

# **ptitech** LED BEACONS

## THE HALOGEN KILLER

The Optitech L.E.D Beacon range has been designed to blend the halogen beacon with L.E.D technology to create a range of products that will change the market forever. Never before has an L.E.D beacon been at or below the price of a halogen beacon with such high quality, durable construction.

## UPGRADED VISIBILITY

- 2x Brighter than SAE standard
- 6 x 5 Watt high powered LEDs
- Proprietary Reflector Optic
- Ultra smooth rotating beam
- Visibility range comparable to 55W or 70W halogen bulb version
- Dual color output (The beacon is designed only to switch between colors not run two colors alternating)




## UPGRADED RELIABILITY

- Virtually unbreakable polycarbonate lens
- SAE Class 1 and ECE R65 TA2 complied
- Non-reflective reflector back
- 10-33V Multi Volt operation
- Reverse polarity protected
- Stepper motor for reliable, quiet operation
- Fully sealed and waterproof (IP67)
- Heavy duty die-cast aluminum base





**KEY FEATURES:****LIGHT COMMERCIAL | COMMERCIAL & CONSTRUCTION****TECHNICAL INFORMATION****10-33**  
VOLTSAE  
CLASS 1CISPR 25  
CLASS 3ECE R65  
APPROVEDECE R10  
APPROVEDISO 21 Grms  
50G SHOCK TESTED

PART#	COLOR	LED	AMP. @12V	WATTAGE	WEIGHT	DIMENSION	ECE APPROVAL
OPT-85660A	Amber	6x5W	1A	30W	0.73lbs	6.06" x 6.06" x 5.47"	ECE R65 TA2, ECE R10
OPT-85660AG	Amber/Green	6x5W	1A	30W	0.73lbs	6.06" x 6.06" x 5.47"	ECE R65 TA2, ECE R10
OPT-85660C	Clear	6x5W	1A	30W	0.73lbs	6.06" x 6.06" x 5.47"	ECE R65 TA2, ECE R10
OPT-85660A	Amber	6x5W	1A	30W	0.73lbs	6.06" x 6.06" x 5.47"	ECE R65 TA2, ECE R10
OPT-85660B	Blue	6x5W	1A	30W	0.73lbs	6.06" x 6.06" x 5.47"	ECE R65 TA2, ECE R10
OPT-85660G	Green	6x5W	1A	30W	0.73lbs	6.06" x 6.06" x 5.47"	ECE R65 TA2, ECE R10
OPT-85660R	Red	6x5W	1A	30W	0.73lbs	6.06" x 6.06" x 5.47"	ECE R65 TA2, ECE R10

**VERSATILE MOUNTING** The Optitech Range is available in 3 Bolt (Flange), Single Bolt, DIN Mount, Flexible Pole Mount and Vacuum Magnetic Mount.**FLANGE**  
PART# : OPT-85660A**SINGLE BOLT**  
PART# : OPT-85662A**FIXED DIN**  
PART# : OPT-85664A**FLEX DIN**  
PART# : OPT-85666A**MAGNETIC BASE**  
PART# : OPT-85668A**5 YEARS**  
FUNCTION WARRANTY  
50,000 HOURS





The vehicle in the image is equipped with:  
TREM-85250A



P/No. TREM-85250A



P/No. TREM-85250AC

# **TREMOR XD** Heavy Duty LED BEACONS

## **BRIGHTER, QUIETER AND MORE DURABLE**

Specifically designed to thrive in the super harsh environment of mines, the Tremor XD Small mining strobes are rated to IP69K and IP67. Featuring a die-cast aluminium base and virtually unbreakable polycarbonate lens, these strobes are made to last. They can be washed with a pressure washer and steam cleaned without compromising the product.

## **5 FLASH PATTERNS**

- Flash rate - rotate at 120 FPM
- Flash rate - single flash at 122 FPM
- Night Mode output - 20%

>>>>> ROTATING >>>>>



SINGLE FLASH (SAE)



ULTRA FLASH

>> ROTATING > ||||| |||||

ROTATOR QUINT FLASH



QUINT FLASH



STEADY ON

## **UPGRADED DURABILITY**

- Military spec vibration resistance
- IP69K ingress protection - allows for pressure washing at heat
- Heavy duty die-cast aluminum base and polycarbonate lens
- Advanced circuitry and high output LEDs
- Smooth external lens to prevent external dust and dirt build up





**KEY FEATURES:****INDUSTRIAL & MINING****TECHNICAL INFORMATION****9-80  
VOLT**SAE  
CLASS 1CISPR 25  
CLASS 3TITLE 13  
CA. APPROVEDMIL SPEC  
VIBRATION RATEDIP69K  
RATED

PART#	LED	AMP. @12V	WATTAGE	WEIGHT	DIMENSION	ECE APPROVAL
TREM-85250A	8x5W	2.0A	40W	1.30lbs	4.92" x 4.92" x 3.58"	ECE R65, ECE R10
TREM-85250AC	8x5W	2.0A	40W	1.30lbs	4.92" x 4.92" x 3.58"	ECE R65, ECE R10

**IMPROVED VISIBILITY**

- 8 Powerful LEDs, SAE Class 1 compliant
- 5 Selectable flash patterns
- Multiple units can be synchronised to flash together
- Ambient Light Sensor automatically dims the output in dark conditions

**5 YEARS**  
FUNCTION WARRANTY  
50,000 HOURS





The vehicle in the image is equipped with:  
TREM-85246A



P/No. TREM-85246A



P/No. TREM-85246AC

# **TREMOR XD** HEAVY DUTY LED BEACONS

## **BRIGHTER, QUIETER AND MORE DURABLE**

Vision X's TREMOR XD L.E.D strobe has been upgraded to be brighter, quieter and more durable. The Tremor XD has been tested in some of the harshest conditions including industrial and mining applications. The Tremor XD has had it's key features significantly increased to now be ideal not only for industrial and above ground mining but also below ground mining applications.

## **7 FLASH PATTERNS**

- Rotates in either direction at 120 RPM
- Night Mode - Day/Night mode switching via third wire



SINGLE FLASH (SAE)



QUAD FLASH (SAE)



QUINT FLASH (SAE)



ULTRA FLASH (SAE)



STEADY ON



ROTATOR (125 RPM) (SAE)



ROTATOR (94 RPM)



ROTATOR QUINT FLASH

## **UPGRADED DURABILITY**

- Military spec vibration resistance
- IP69K ingress protection - allows for pressure washing at heat
- Heavy duty die-cast aluminum base and polycarbonate lens
- Advanced circuitry and high output LEDs
- Smooth external lens to prevent external dust and dirt build up





**KEY FEATURES:****INDUSTRIAL & MINING****TECHNICAL INFORMATION****12/24**  
VOLT

PART#	LED	AMP. @12V	WATTAGE	WEIGHT	DIMENSION	ECE APPROVAL
TREM-85246A	16x3W	1.85A	48W	2.20lbs	6.57" x 6.57" x 6.57"	ECE R10
TREM-85246AC	16x3W	1.85A	48W	2.20lbs	6.57" x 6.57" x 6.57"	ECE R10

**ULTIMATE VISIBILITY**

Improved optical design ensures extreme visibility for ultra safe worksites

- Rotate pattern is up to 5x more visible than the competition
- Strobe pattern is up to 3x more visible than the competition.

Precision optic ensures the Tremor XD meets and exceeds SAE Class 1 in both flash and rotate (76% brighter than SAE minimum)

Optical precision provides a smooth rotating pattern that ensures optimal visibility and SAE Class 1 compliance. This is market leading as most strobes do not pass SAE for rotate

Includes 2 rotate patterns (clockwise and counter clockwise) for increased visual effect

Single upward facing high power LED provides significant increase in upward illumination - ideal on sides with tall vehicles.

**5 YEARS**  
FUNCTION WARRANTY  
50,000 HOURS

## VISION X HEADQUARTERS

1601 Boundary Blvd  
Auburn WA, 98001  
United States of America  
P: 253-218-2900



**VISION X**  
[visionxlighting.com](http://visionxlighting.com)

**INDUSTRIAL**  
[vxindustrial.com](http://vxindustrial.com)

**STRUCTURAL**  
[vxstructural.com](http://vxstructural.com)

**MARITIME**  
[vxmaritime.com](http://vxmaritime.com)



COPYRIGHT 2023 VISION X LIGHTING